

In the claims:

1. (currently amended) Wiper blade for window panes in motor vehicles, comprising an elongated rubber-elastic wiping strip (20) which can contact the window pane (14) and is provided at both of its longitudinal sides (30) with open-edged longitudinal receiving grooves (32) which are arranged in a plane approximately parallel to the window pane ~~and in which and~~ forming a longitudinal web (36) therebetween; a carrying element formed by at least two strip-shaped elongated, resilient separate carrying rails (12) are accommodated in ~~each instance~~ the grooves (32), the inner edges of the carrying rails (12) which face one another contact ~~at the~~ longitudinal web (36) of the wiping strip ~~remaining between the grooves (32) and the two carrying rails (12) are secured in their receiving~~ the grooves (32) transverse to their longitudinal extension; by a connection device formed as a holder (16) which secures the carrying rails (12) in the grooves (32) and is provided with means for connection of a wiper arm and arranged at an upper strip surfaces (13) of the carrying rails remote of the window pane, wherein the holder is provided with L-shaped claws (46) each having two legs with a first L-leg (48) traversing the outer edges (52) of the carrying rails and the a second L-leg (50) engaging under the respective carrying rail (12) and a distance (60) measured transverse to the longitudinal extension of the wiper blade (10)

between the inner edges of the first L-leg (48) which face one another at least in a region of the L-legs is less than the sum of the width (62) of the two carrying rails (12) plus the width (46) of the longitudinal web (36) of the wiping strip (20), whereby the wiper strip (20) provided with the carrying rails (12) is held by compression produced in the longitudinal web (36), wherein said carrying element has a lower side on which the wiper strip (20) is directly placeable and an upper side on which said connection device is directly placed.

2. (previously presented) Wiper blade according to claim 1, wherein each of the two carrying rails (12) projects out of its receiving groove (32) at least along a longitudinal portion by an edge strip, and in that the second L-legs (50) engage the lower strip surface (19) of their carrying rails (12) which faces the window pane (14).

3. (previously presented) Wiper blade according to claims 1, wherein the holder (16) has a plate-shaped body (42) which is supported at the upper strip surfaces (13) of the carrying rails (12), the first L-legs (48) of the claws (46) being connected with longitudinal sides (44) of this plate-shaped body (42) that are located opposite one another.

4. (previously presented) Wiper blade according to claim 1, wherein the claws (46) are arranged at the longitudinal sides (44) by pairs located opposite one another.

5. (previously presented) Wiper blade according to claim 3, wherein the body (42) of the holder (16) is provided at its underside facing the upper strip surfaces (13) of the two carrying rails (12) with a longitudinal cutout (54) for receiving a cover strip (40) of the wiping strip (20) defining the width of the two receiving grooves (32).

6. (Previously presented) Wiper blade according to claim 1, wherein the holder (16) is provided with means (48) for connecting the wiper arm (18).

7. (Previously presented) Wiper blade according to claim 1, wherein the lower strip surfaces (19) of the two carrying rails (12) together enclose an angle (α) that is less than 180°.

8. (Previously presented) Wiper blade according to claim 1, wherein the holder (16) is made of plastic.

9. (Previously presented) Wiper blade according to claim 1, wherein the holder (16) is made of metal.

10. (Previously presented) Wiper blade according to claim 1, wherein each carrying rail (112, 212, 312, respectively) is provided with at least one projection (116, 216, 316, respectively) at its inner longitudinal edges (114, 214, 314, respectively) facing the longitudinal web (36) of the wiping strip (20).

11. (previously presented) Wiper blade according to claim 10, wherein in that the projection (116) of one carrying rail (112) is located opposite to the projection (116) of the other carrying rail (112).

12. (previously presented) Wiper blade according to claim 10, wherein the projection (216) of one carrying rail (212) is arranged so as to be offset with respect to the projection (216) of the other carrying rail (212) in its longitudinal direction.

13. (previously presented) Wiper blade according to claim 10, wherein a recess (318) of one carrying rail (312 or 313) is located opposite to the projection (316) of the other carrying rail (312 or 313).

14. (Currently amended) Method for mounting a wiper blade constructed in accordance with ~~one of claims 1 to 13~~ claim 1, characterized in that the carrying rails (12) are introduced into their receiving grooves (32) and their upper strip surfaces (13) are tilted relative to one another in such a way that, together, they enclose an angle (β) of less than 180° , in that the carrying rails (12) are then inserted together with the wiping strip (20) into the existing space (80) between the claws (46) arranged at the oppositely located longitudinal sides (44) of the holder (16), in which space (80) the carrying rails (12), when released, automatically attain their operating position and are fixed in the holder (16) together with the wiping strip (20) by the resulting compression of the longitudinal web (36).

15. (New) A wiper system for window panes of motor vehicles, comprising a wiper arm; and a wiper blade mountable on the wiper arm and including an elongated rubber-elastic wiping strip (20) which can contact the window pane (14) and is provided at both of its longitudinal sides (30) with open-edged longitudinal receiving grooves (32) which are arranged in a plane approximately parallel to the window pane and forming a longitudinal web (36) therebetween; a carrying element formed by at least two strip-shaped elongated, resilient separate carrying rails (12) accommodated in the grooves (32), the inner edges of the carrying rails (12) which face one another contact the longitudinal web (36) of the wiping strip and the two carrying rails (12) are secured in the grooves (32) transverse to their

longitudinal extension; a connection device formed as a holder (16) which secures the carrying rails (12) in the grooves (32) and is provided with means for connection of a wiper arm, wherein the holder is provided with L-shaped claws (46) each having two legs with a first L-leg (48) traversing outer edges (52) of the carrying rails and a second L-leg (50) engaging under the respective carrying rail (12) and a distance (60) measured transverse to the longitudinal extension of the wiper blade (10) between inner edges of the first L-leg (48) which face one another at least in a region of the L-legs is less than a sum of a width (62) of the two carrying rails (12) plus a width (46) of the longitudinal web (36) of the wiping strip (20), whereby the wiper strip (20) provided with the carrying rails (12) is held by compression produced in the longitudinal web (36), wherein said carrying element has a lower side on which the wiper strip (20) is directly placed and an upper side on which said connection device is directly placed.